

MISCELLANEOUS

Lay-in Grounding Lugs

Features:


- Each lug takes a range of cable sizes
- Heavy duty slotted or hex head screw
- Aluminum layin lugs are suitable for use with copper or aluminum conductors
- Copper layin lugs are suitable for use with copper or aluminum conductors

Standard Materials:
Aluminum or
Copper

Standard Finish:
Aluminum Lug - Zinc plated
Copper Lug - Natural

Applicable Third Party
Standards:
UL Standard: 467
Fed. Spec. W-F-408E
NEMA: FB-1



* UL Listed
^ Not UL Certified



4/14AL and 1/0-8AL furnished with slotted screw. 3/0-6AL and 250MCM-6AL furnished with hex head screw

Aluminum Lugs

CATALOG NUMBER	LUG SIZE	DIM A	DIM B	DIM C	PCS/UNITS PER BOX	WEIGHT PER C
* 4-14AL	4-14	1-1/16"	3/8"	3/4"	1500	1.9
* 1/0-8AL	1/0-8	1-1/2"	5/8"	1-1/8"	480	6.6
* 3/0-6AL	3/0-6	2"	13/16"	1-1/2"	198	16.4
^ 250MCM-6AL	250MCM-6	2-3/16"	13/16"	1-11/16"	180	18.8



4/14CL and 1/0-8CL furnished with slotted screw. 3/0-6CL and 250MCM-6CL furnished with hex head screw

Copper Lugs

CATALOG NUMBER	LUG SIZE	DIM A	DIM B	DIM C	PCS/UNITS PER BOX	WEIGHT PER C
* 4-14CL	4-14	1-1/16"	3/8"	3/4"	720	4.4
* 1/0-8CL	1/0-8	1-1/2"	5/8"	1-1/8"	200	15.9
* 3/0-6CL	3/0-6	2"	13/16"	1-1/2"	84	40.0
^ 250MCM-6CL	250MCM-6	2-3/16"	13/16"	1-11/16"	72	50.3

