

Steel Locknut

Grounding Locknut

Steel, Sealing, Grounding, and Aluminum Locknuts

Features

- Six tab design for easy gripping
- Tabs provide bonding continuity

Standard Materials

- Steel or Aluminum

Standard Finish

- Zinc plated (steel)

Applicable Third Party Standards

- UL Standard 514B
- CSA Standard C22.2 No. 18.3
- NEMA FB-1



Steel Locknut

Catalog Number	Trade Size (in)	Dim A (in)	Dim B (in)	Thread Pitch Diameter	Thread Minor Diameter Min.	Tabs	TPI	Inner Pack	Master Pack	Weight Per C (lb)
10KON	3/8"	0.875	0.125	.644-.650	0.625	-	18	100	1000	1.1
11KON	1/2"	1.140	0.125	.800-.810	0.769	6	14	100	1000	1.2
12KON	3/4"	1.420	0.125	1.010-1.020	0.978	6	14	100	1000	1.9
13KON	1"	1.770	0.170	1.265-1.275	1.228	6	11-1/2	100	500	3.3
14KON	1-1/4"	2.281	0.170	1.610-1.620	1.573	6	11-1/2	100	500	4.6
15KON	1-1/2"	2.598	0.170	1.850-1.860	1.813	6	11-1/2	50	250	5.3
16KON	2"	3.175	0.170	2.322-2.332	2.285	6	11-1/2	50	250	7.3
17KON	2-1/2"	3.562	0.375	2.804-2.816	2.770	6	8	25	250	10.7
18KON	3	4.250	0.375	3.429-3.441	3.395	6	8	25	125	14.9
19KON	3-1/2"	4.803	0.375	3.929-3.941	3.895	6	8	10	50	18.4
20KON	4"	5.402	0.375	4.429-4.441	4.395	6	8	10	50	22.4
21KON	5"	6.674	0.500	5.488-5.500	5.420	6	8	NA	20	77.1
22KON	6"	7.934	0.562	6.545-6.557	6.480	6	8	NA	10	98.3

Grounding Locknut

Catalog Number	Trade Size (in)	Dim A (in)	Dim B (in)	Thread Pitch Diameter	Thread Minor Diameter Min.	Tabs	TPI	Inner Pack	Master Pack	Weight Per C (lb)
GL11KON	1/2"	1.350	0.125	.800-.810	0.769	6	14	100	1000	2.4
GL12KON	3/4"	1.580	0.140	1.010-1.020	0.978	6	11-1/2	50	500	2.9
GL13KON	1"	1.880	0.170	1.265-1.275	1.228	6	11-1/2	50	500	4.2
GL14KON	1-1/4"	2.300	0.170	1.610-1.620	1.573	6	11-1/2	50	250	5.5
GL15KON	1-1/2"	2.600	0.170	1.850-1.860	1.813	6	11-1/2	50	250	6.6
GL16KON	2"	3.100	0.187	2.322-2.332	2.285	6	8	25	125	11.5
GL17KON	2-1/2"	3.562	0.375	2.804-2.816	2.770	6	8	20	100	26.5
GL18KON	3	4.250	0.375	3.429-3.441	3.395	6	8	10	50	37.5
GL19KON	3-1/2"	4.803	0.438	3.929-3.941	3.895	6	8	10	50	43.4
GL20KON	4"	5.402	0.438	4.429-4.441	4.395	6	8	5	25	49.8



Locknuts

Steel, Sealing, Grounding, and Aluminum Locknuts

Features

- Six tab design for easy gripping
- Tabs provide bonding continuity

Standard Materials


- Steel or Aluminum

Standard Finish


- Zinc plated (steel)

Applicable Third Party Standards

- UL Standard 514B
- CSA Standard C22.2 No. 18.3
- NEMA FB-1



Sealing Locknut



Aluminum Locknut



Sealing Locknut

Catalog Number	Trade Size (in)	Dim A (in)	Dim B (in)	Thread Pitch Diameter	Thread Minor Diameter Min.	Tabs	TPI	Inner Pack	Master Pack	Weight Per C (lb)
SL11KON	1/2"	1.140	0.125	.800-.810	0.769	6	14	100	1000	1.3
SL12KON	3/4"	1.420	0.125	1.010-1.020	0.978	6	14	50	500	2
SL13KON	1"	1.770	0.170	1.265-1.275	1.228	6	11-1/2	100	500	3.5
SL14KON	1-1/4"	2.281	0.170	1.610-1.620	1.573	6	11-1/2	50	250	4.9
SL15KON	1-1/2"	2.598	0.170	1.850-1.860	1.813	6	11-1/2	50	250	5.7
SL16KON	2"	3.175	0.170	2.322-2.332	2.285	6	11-1/2	25	125	7.9
SL17KON	2-1/2"	3.562	0.375	2.804-2.816	2.770	6	8	25	125	12.3
SL18KON	3	4.250	0.375	3.429-3.441	3.395	6	8	25	50	16.3
SL19KON	3-1/2"	4.803	0.375	3.929-3.941	3.895	6	8	25	50	20.2
SL20KON	4"	5.402	0.375	4.429-4.441	4.395	6	8	25	50	24.3
SL21KON	5"	6.674	0.375	5.488-5.500	5.430	6	8	NA	10	81.8
SL22KON	6"	7.934	0.375	6.454-6.557	6.486	6	8	NA	10	104.9

Aluminum Locknut

Catalog Number	Trade Size (in)	Dim A (in)	Dim B (in)	Thread Pitch Diameter	Thread Minor Diameter Min.	Tabs	TPI	Inner Pack	Master Pack	Weight Per C (lb)
AL11KON	1/2"	1.140	0.170	.800-.810	0.769	6	14	NA	100	0.6
AL12KON	3/4"	1.420	0.170	1.010-1.020	0.978	6	14	NA	100	0.8
AL13KON	1"	1.770	0.170	1.265-1.275	1.228	6	11-1/2	NA	50	1.1
AL14KON	1-1/4"	2.281	0.170	1.610-1.620	1.573	6	11-1/2	NA	100	1.5
AL15KON	1-1/2"	2.598	0.170	1.850-1.860	1.813	6	11-1/2	NA	50	1.7
AL16KON	2"	3.175	0.187	2.322-2.332	2.285	6	11-1/2	NA	50	2.8
AL17KON	2-1/2"	3.562	0.170	2.804-2.816	2.770	6	8	NA	20	8.5
AL18KON	3	4.250	0.170	3.429-3.441	3.395	6	8	NA	10	11.6
AL19KON	3-1/2"	4.803	0.170	3.929-3.941	3.895	6	8	NA	10	14.3
AL20KON	4"	5.402	0.170	4.429-4.441	4.395	6	8	NA	5	17.1