

UNF, UNL, UNY, UNA unions and EL elbows

Cl. I, Div. 1 & 2, Groups C, D
Cl. II, Div. 1, Groups E, F, G
Cl. II, Div. 2, Groups F, G
Cl. III

Explosionproof
Dust-ignitionproof

4F

Ordering information (continued):

UNA



Male
(with removable nipple)

Male	
Hub size	Cat. #
1/2"	UNA16
3/4"	UNA26
1"	UNA36

EL



90° male



90° female



45° female



90° male and female

90° male

Hub size	Cat. #
1/2"	EL195
3/4"	EL295
1"	EL395

45° female

Hub size	Cat. #
1/2"	EL1
3/4"	EL2
1"	EL3
1 1/4"	EL4
1 1/2"	EL5
2"	EL6
2 1/2"	EL7
3"	EL8
3 1/2"	EL9
4"	EL10


90° female

Hub size	Cat. #
1/2"	EL19 ^F
3/4"	EL29 ^F
1"	EL39 ^F
1 1/4"	EL49 ^F
1 1/2"	EL59 ^F
2"	EL69 ^F
2 1/2"	EL79


90° male and female

Hub size	Cat. #
1/2"	EL196 ^F
3/4"	EL296 ^F
1"	EL396 ^F
1 1/4"	EL496


Dimensions (in inches):




90° male



90° female



45° female



90° male and female

EL

UNA

Male

Hub size	Length	Width
1/2"	4 ⁵ / ₁₆	2 ⁵ / ₈
3/4"	4 ¹³ / ₁₆	2 ⁷ / ₈
1"	5 ¹¹ / ₁₆	3 ¹ / ₂

EL

Hub size	45° female	90° male	90° female	90° male and female
	a	a	a	a
1/2"	1 ³ / ₁₆	1 ¹ / ₁₆	1 ¹⁷ / ₃₂	1 ¹⁷ / ₃₂
3/4"	1 ³ / ₈	1 ⁵ / ₈	1 ³ / ₄	1 ⁵ / ₈
1"	1 ²¹ / ₃₂	1 ⁷ / ₈	2	1 ⁷ / ₈
1 1/4"	1 ³ / ₄	2 ¹ / ₄	2 ¹ / ₈	2 ¹ / ₈
1 1/2"	1 ¹⁵ / ₁₆	4		
2"	2 ¹ / ₄	5		
2 1/2"	2 ³ / ₄	6 ⁷ / ₁₆		
3"	3 ³ / ₈			
3 1/2"	3 ⁷ / ₈			
4"	3 ⁷ / ₈			

^F See Certifications and compliances section for classification of each product.

^F Available in copper-free aluminum. To order, add suffix 'SA' to end of catalog number.