

CONDUIT BODIES

Aluminum Die Cast Threaded LB Conduit Bodies For Rigid • IMC conduit

Application:

To provide access to conductors for pulling, splicing and maintenance.

Features:


- Tapered threaded hubs - NPT
- Suitable for use in concrete
- Wet location

Standard Materials:


Die cast Aluminum
Copper free
Covers - Stamped aluminum
Gasket - Neoprene rubber

Applicable Third Party

Standards:
UL Standard: 514A
Fed. Spec. W-C-586D
NEMA: FB-1



CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	PCS/UNITS PER BOX	WEIGHT PER C
ALB1	1/2"	4-5/16"	1-5/16"	2-3/16"	100	24.3
ALB2	3/4"	5-1/16"	1-9/16"	2-7/16"	50	37.2
ALB3	1"	5-7/8"	1-3/4"	2-3/4"	25	46.3
ALB4	1-1/4"	7-13/16"	2-1/2"	3-7/16"	10	97.7
ALB5	1-1/2"	7-13/16"	2-1/2"	3-7/16"	10	90.9
ALB6	2"	10-1/16"	3-1/8"	4-5/16"	5	221.6
ALB7	2-1/2"	12-13/16"	4-1/2"	5-5/16"	1	365.7
ALB8	3"	12-13/16"	4-1/2"	5-15/16"	1	429.7
ALB9	3-1/2"	15-5/8"	5-9/16"	7-1/16"	1	936.9
ALB10	4"	15-5/8"	5-9/16"	7-1/16"	1	851.4



Aluminum Die Cast Threaded LB Conduit Bodies with
Stamped Aluminum Cover & Neoprene Gasket

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	PCS/UNITS PER BOX	WEIGHT PER C
ALB1CG	1/2"	4-5/16"	1-5/16"	2-7/16"	100	30.5
ALB2CG	3/4"	5-1/16"	1-9/16"	2-11/16"	50	44.6
ALB3CG	1"	5-7/8"	1-3/4"	3"	25	56.3
ALB4CG	1-1/4"	7-13/16"	2-1/2"	3-11/16"	10	116.8
ALB5CG	1-1/2"	7-13/16"	2-1/2"	3-11/16"	10	110.0
ALB6CG	2"	10-1/16"	3-1/8"	4-9/16"	5	253.9
ALB7CG	2-1/2"	12-13/16"	4-1/2"	5-9/16"	1	427.4
ALB8CG	3"	12-13/16"	4-1/2"	6-3/16"	1	491.4
ALB9CG	3-1/2"	15-5/8"	5-9/16"	7-5/16"	1	1060.1
ALB10CG	4"	15-5/8"	5-9/16"	7-5/16"	1	974.6



CONDUIT BODIES

Aluminum Die Cast Theaded C Conduit Bodies For Rigid • IMC conduit

Application:

To provide access to conductors for pulling, splicing and maintenance.

Features:


- Tapered threaded hubs - NPT
- Suitable for use in concrete
- Wet Location

Standard Materials:


Die cast aluminum
Copper free
Covers - Stamped aluminum
Gasket - Neoprene rubber

Applicable Third Party Standards:

UL Standard: 514A
Fed. Spec. W-C-586D
NEMA: FB-1



CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	PCS/UNITS PER BOX	WEIGHT PER C
AC1	1/2"	4-11/16"	1-3/8"	1-5/16"	100	21.3
AC2	3/4"	5-1/2"	1-9/16"	1-5/8"	50	33.1
AC3	1"	6-7/16"	1-3/4"	1-7/8"	25	46.3
AC4	1-1/4"	8-5/16"	2-1/2"	2-1/2"	10	81.9
AC5	1-1/2"	8-3/8"	2-1/2"	2-1/2"	10	85.0
AC6	2"	10-5/16"	3-3/16"	3-3/8"	5	187.5
AC7	2-1/2"	13-1/8"	4-1/2"	4"	1	325.0
AC8	3"	13-3/16"	4-9/16"	4-9/16"	1	398.8
AC9	3-1/2"	16-1/8"	5-11/16"	5-5/8"	1	975.0
AC10	4"	16-1/8"	5-11/16"	5-5/8"	1	875.0



Aluminum Die Cast Threaded C Conduit Bodies with
Stamped Aluminum Cover & Neoprene Gasket

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	PCS/UNITS PER BOX	WEIGHT PER C
AC1CG	1/2"	4-11/16"	1-3/8"	1-9/16"	100	27.5
AC2CG	3/4"	5-1/2"	1-9/16"	1-3/4"	50	40.5
AC3CG	1"	6-7/16"	1-3/4"	2-1/8"	25	56.3
AC4CG	1-1/4"	8-5/16"	2-1/2"	2-3/4"	10	101.0
AC5CG	1-1/2"	8-3/8"	2-1/2"	2-3/4"	10	104.1
AC6CG	2"	10-5/16"	3-3/16"	3-5/8"	5	219.8
AC7CG	2-1/2"	13-1/8"	4-1/2"	4-1/4"	1	386.7
AC8CG	3"	13-3/16"	4-9/16"	4-13/16"	1	460.5
AC9CG	3-1/2"	16-1/8"	5-11/16"	6"	1	1098.2
AC10CG	4"	16-1/8"	5-11/16"	6"	1	998.2



CONDUIT BODIES

Aluminum Die Cast Threaded LL Conduit Bodies For Rigid • IMC conduit

Application:

To provide access to conductors for pulling, splicing and maintenance.

Features:


- Tapered threaded hubs - NPT
- Suitable for use in concrete
- Wet Location

Standard Materials:


Die cast aluminum
Copper free
Covers - Stamped aluminum
Gasket - Neoprene rubber

Applicable Third Party

Standards:
UL Standard: 514A
Fed. Spec. W-C-586D
NEMA: FB-1



CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	PCS/UNITS PER BOX	WEIGHT PER C
ALL1	1/2"	4-5/16"	2-1/16"	1-3/8"	100	24.5
ALL2	3/4"	5-1/16"	2-1/4"	1-5/8"	50	36.8
ALL3	1"	5-7/8"	2-5/8"	1-7/8"	25	45.2
ALL4	1-1/4"	7-13/16"	3-5/8"	2-1/2"	10	97.9
ALL5	1-1/2"	7-13/16"	3-5/8"	2-1/2"	10	91.9
ALL6	2"	10-1/16"	4-7/16"	3-3/8"	5	245.0
ALL7	2-1/2"	12-13/16"	5-3/4"	4"	1	387.6
ALL8	3"	12-13/16"	5-3/4"	4-1/2"	1	439.2
ALL9	3-1/2"	15-5/8"	7-11/16"	5-5/8"	1	923.7
ALL10	4"	15-5/8"	7-11/16"	5-5/8"	1	881.8



Aluminum Die Cast Threaded LL Conduit Bodies with
Stamped Aluminum Cover & Neoprene Gasket

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	PCS/UNITS PER BOX	WEIGHT PER C
ALL1CG	1/2"	4-5/16"	2-1/16"	1-5/8"	100	30.7
ALL2CG	3/4"	5-1/16"	2-1/4"	1-7/8"	50	44.2
ALL3CG	1"	5-7/8"	2-5/8"	2-1/8"	25	55.2
ALL4CG	1-1/4"	7-13/16"	3-5/8"	2-3/4"	10	117.0
ALL5CG	1-1/2"	7-13/16"	3-5/8"	2-3/4"	10	111.0
ALL6CG	2"	10-1/16"	4-7/16"	3-5/8"	5	277.3
ALL7CG	2-1/2"	12-13/16"	5-3/4"	4-1/4"	1	419.9
ALL8CG	3"	12-13/16"	5-3/4"	4-3/4"	1	500.9
ALL9CG	3-1/2"	15-5/8"	7-11/16"	5-7/8"	1	1046.9
ALL10CG	4"	15-5/8"	7-11/16"	5-7/8"	1	1005.0



CONDUIT BODIES

Aluminum Die Cast Threaded LR Conduit Bodies For Rigid • IMC conduit

Application:

To provide access to conductors for pulling, splicing and maintenance.

Features:


- Tapered threaded hubs - NPT
- Suitable for use in concrete
- Wet location

Standard Materials:


Die cast aluminum
Copper free
Covers - Stamped aluminum
Gasket - Neoprene rubber

Applicable Third Party

Standards:
UL Standard: 514A
Fed. Spec. W-C-586D
NEMA: FB-1



CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	PCS/UNITS PER BOX	WEIGHT PER C
ALR1	1/2"	4-5/16"	2-1/16"	1-3/8"	100	22.7
ALR2	3/4"	5-1/16"	2-1/4"	1-5/8"	50	37.5
ALR3	1"	5-7/8"	2-5/8"	1-7/8"	25	48.7
ALR4	1-1/4"	7-13/16"	3-5/8"	2-1/2"	10	98.1
ALR5	1-1/2"	7-13/16"	3-5/8"	2-1/2"	10	93.9
ALR6	2"	10-1/16"	4-7/16"	3-3/8"	5	253.5
ALR7	2-1/2"	12-13/16"	5-3/4"	4"	1	366.2
ALR8	3"	12-13/16"	5-3/4"	4-1/2"	1	406.3
ALR9	3-1/2"	15-5/8"	7-11/16"	5-5/8"	1	928.1
ALR10	4"	15-5/8"	7-11/16"	5-5/8"	1	901.7



Aluminum Die Cast Threaded LR Conduit Bodies with
Stamped Aluminum Cover & Neoprene Gasket

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	PCS/UNITS PER BOX	WEIGHT PER C
ALR1CG	1/2"	4-5/16"	2-1/16"	1-5/8"	100	28.9
ALR2CG	3/4"	5-1/16"	2-1/4"	1-7/8"	50	44.9
ALR3CG	1"	5-7/8"	2-5/8"	2-1/8"	25	58.7
ALR4CG	1-1/4"	7-13/16"	3-5/8"	2-3/4"	10	117.2
ALR5CG	1-1/2"	7-13/16"	3-5/8"	2-3/4"	10	113.0
ALR6CG	2"	10-1/16"	4-7/16"	3-5/8"	5	285.8
ALR7CG	2-1/2"	12-13/16"	5-3/4"	4-1/4"	1	427.9
ALR8CG	3"	12-13/16"	5-3/4"	4-3/4"	1	468.0
ALR9CG	3-1/2"	15-5/8"	7-11/16"	5-7/8"	1	1051.3
ALR10CG	4"	15-5/8"	7-11/16"	5-7/8"	1	1024.9



CONDUIT BODIES

Aluminum Die Cast Threaded T Conduit Bodies For Rigid • IMC conduit


Application:
To provide access to
conductors for pulling, splicing
and maintenance.

Features:


- Tapered threaded hubs - NPT
- Suitable for use in concrete
- Wet location

Standard Materials:
Die cast aluminum
Copper free
Covers - Stamped aluminum
Gasket - Neoprene rubber

**Applicable Third Party
Standards:**
UL Standard: 514A
Fed. Spec. W-C-586D
NEMA: FB-1



CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	PCS/UNITS PER BOX	WEIGHT PER C
AT1	1/2"	4-3/4"	2-1/16"	1-3/8"	100	23.2
AT2	3/4"	5-9/16"	2-1/4"	1-5/8"	50	37.5
AT3	1"	6-7/16"	2-5/8"	1-7/8"	25	53.3
AT4	1-1/4"	8-1/4"	3-9/16"	2-1/2"	10	99.9
AT5	1-1/2"	8-3/8"	3-9/16"	2-1/2"	10	97.6
AT6	2"	10-11/16"	4-3/8"	3-1/8"	5	264.5
AT7	2-1/2"	13-1/4"	5-3/4"	4"	1	374.8
AT8	3"	13-1/4"	5-3/4"	4-1/2"	1	444.2
AT9	3-1/2"	16-1/8"	7-11/16"	5-5/8"	1	1146.4
AT10	4"	16-1/8"	7-11/16"	5-5/8"	1	1079.2



Aluminum Die Cast Threaded T Conduit Bodies with
Stamped Aluminum Cover & Neoprene Gasket

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	PCS/UNITS PER BOX	WEIGHT PER C
AT1CG	1/2"	4-3/4"	2-1/16"	1-5/8"	100	29.4
AT2CG	3/4"	5-9/16"	2-1/4"	1-7/8"	50	44.9
AT3CG	1"	6-7/16"	2-5/8"	2-1/8"	25	63.3
AT4CG	1-1/4"	8-1/4"	3-9/16"	2-3/4"	10	119.0
AT5CG	1-1/2"	8-3/8"	3-9/16"	2-3/4"	10	116.7
AT6CG	2"	10-11/16"	4-3/8"	3-5/8"	5	296.8
AT7CG	2-1/2"	13-1/4"	5-3/4"	4-1/4"	1	436.5
AT8CG	3"	13-1/4"	5-3/4"	4-3/4"	1	505.9
AT9CG	3-1/2"	16-1/8"	7-11/16"	5-7/8"	1	1269.6
AT10CG	4"	16-1/8"	7-11/16"	5-7/8"	1	1202.4



CONDUIT BODIES

Aluminum Die Cast Threaded TB Conduit Bodies For Rigid • IMC conduit

Application:

To provide access to conductors for pulling, splicing and maintenance.

Features:


- Tapered threaded hubs - NPT
- Suitable for use in concrete
- Wet location

Standard Materials:


Die cast aluminum
Copper free
Covers - Stamped aluminum
Gasket - Neoprene rubber

Applicable Third Party

Standards:
UL Standard: 514A
Fed. Spec. W-C-586D
NEMA: FB-1



CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	PCS/UNITS PER BOX	WEIGHT PER C
ATB1	1/2	4-3/4"	1-3/8"	2-1/8"	100	29.1
ATB2	3/4"	5-1/2"	1-9/16"	2-3/8"	50	42.3
ATB3	1"	6-1/2"	1-13/16"	2-3/4"	25	58.2
ATB4	1-1/4"	8-1/4"	2-7/16"	3-1/2"	10	110.3
ATB5	1-1/2"	8-1/4"	2-7/16"	3-1/2"	10	108.8
ATB6	2"	10-1/2"	3-3/16"	4-1/2"	5	192.2



Aluminum Die Cast Threaded TB Conduit Bodies with Stamped Aluminum Cover & Neoprene Gasket

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	PCS/UNITS PER BOX	WEIGHT PER C
ATB1CG	1/2"	4-3/4"	1-3/8"	2-3/8"	100	34.8
ATB2CG	3/4"	5-1/2"	1-9/16"	2-5/8"	50	49.2
ATB3CG	1"	6-1/2"	1-13/16"	3"	25	67.7
ATB4CG	1-1/4"	8-1/4"	2-7/16"	3-3/4"	10	128.4
ATB5CG	1-1/2"	8-1/4"	2-7/16"	3-3/4"	10	126.9
ATB6CG	2"	10-1/2"	3-3/16"	4-3/4"	5	222.5



CONDUIT BODIES

Aluminum Die Cast Threaded X Conduit Bodies For Rigid • IMC conduit

Application:

To provide access to conductors for pulling, splicing and maintenance.

Features:

- Tapered threaded hubs - NPT
- Suitable for use in concrete
- Wet location


Standard Materials:

Die cast aluminum
Copper free
Covers - Stamped aluminum
Gasket - Neoprene rubber


Applicable Third Party

Standards:

UL Standard: 514A
Fed. Spec. W-C-586D
NEMA: FB-1



CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	PCS/UNITS PER BOX	WEIGHT PER C
AX1	1/2"	4-3/4"	2-11/16"	1-3/8"	100	31.4
AX2	3/4"	5-1/2"	3"	1-5/8"	50	47.1
AX3	1"	6-1/2"	3-1/2"	1-7/8"	25	61.9
AX4	1-1/4"	8-1/4"	4-1/2"	2-1/2"	10	117.7
AX5	1-1/2"	8-1/4"	4-1/2"	2-1/2"	10	117.9
AX6	2"	10-1/2"	5-3/8"	3-3/8"	5	212.5



Aluminum Die Cast Threaded X Conduit Bodies with
Stamped Aluminum Cover & Neoprene Gasket

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	PCS/UNITS PER BOX	WEIGHT PER C
AX1CG	1/2"	4-3/4"	2-11/16"	1-5/8"	100	37.1
AX2CG	3/4"	5-1/2"	3"	1-7/8"	50	54.0
AX3CG	1"	6-1/2"	3-1/2"	2-1/8"	25	71.4
AX4CG	1-1/4"	8-1/4"	4-1/2"	2-3/4"	10	135.8
AX5CG	1-1/2"	8-1/4"	4-1/2"	2-3/4"	10	136.0
AX6CG	2"	10-1/2"	5-3/8"	3-5/8"	5	242.8

